

HIGHTEC SCHALÖL 2000

Moulding oil for metals and timber formworks

Description

HIGHTEC SCHALÖL 2000 is a highly effective, non-emulsive moulding oil for undiluted use in metals and timber formworks in the concrete goods and artificial stone industry and during production of pre-stressed concrete.

Apply by spraying or spreading on. The formwork can be moistened with the oil a few days prior to or shortly before concreting.

Advantages

- Good creep capability
- Simple and clean form removal
- Sets well
- Smooth surfaces with sharp contoured edges with the most economical use



Typical characteristics

Property	Method	Unit	Value
Density at 15 °C	ASTM D-7042	g/ml	0.87
Kinematic viscosity KV 40	ASTM D-7042	mm ² /s	18
Flash point	ASTM D-92 / DIN EN ISO 2592	°C	>140
Pour point	ASTM D-97 / DIN EN ISO 3016	°C	-33

These characteristics are typical for current production. The data does not constitute an assurance of properties or a guarantee of suitability for a specific application. Existing legal provisions and regulations that affect handling and usage of the products must be observed by the recipient of our products. ROWE products are continuously being developed. For this reason, ROWE retains the right to change all technical data in this product information at any time without prior announcement. Our current General Delivery and Payment Conditions apply (www.rowe-oil.com).

